

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
9 September 2005 (09.09.2005)

PCT

(10) International Publication Number
WO 2005/082646 A1

(51) International Patent Classification⁷: **B60C 23/04**,
17/00, B29C 73/16

Schwaigern 74193 (DE). **KLEMPAU, Frank** [DE/DE];
Salzaeckerstr. 18, Stuttgart 70567 (DE).

(21) International Application Number:
PCT/JP2004/019691

(74) Agent: **SUGIMURA, Kosaku**; 7F, Kazan Building, 2-4,
Kasumigaseki 3-chome, Chiyoda-ku, Tokyo 1000013 (JP).

(22) International Filing Date:
22 December 2004 (22.12.2004)

(81) Designated States (*unless otherwise indicated, for every
kind of national protection available*): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ,
TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA,
ZM, ZW.

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2004-056658 1 March 2004 (01.03.2004) JP

(84) Designated States (*unless otherwise indicated, for every
kind of regional protection available*): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,
SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN,
GQ, GW, ML, MR, NE, SN, TD, TG).

(71) Applicants (*for all designated States except US*):
BRIDGESTONE CORPORATION [JP/JP]; 10-1,
Kyobashi 1-chome, Chuo-ku, Tokyo 1048340 (JP).
DAIMLER CHRYSLER AG [DE/DE]; Epplestrasse
225, Stuttgart 70567 (DE).

(72) Inventors; and

(75) Inventors/Applicants (*for US only*): **WATANABE**,
Shinichi [JP/JP]; c/o Bridgestone Corporation, Tech-
nical Center, 3-1-1, Ogawahigashi-cho, Kodaira-shi,
Tokyo 1878531 (JP). **KNOTHE, Frank** [DE/DE]; Teure-
mertalweg 13, Gerlingen 70839 (DE). **RUNTSCH**,
Gerd [DE/DE]; Zavelsteinweg 2, Remseck 71686 (DE).
LEISTER, Guenter [DE/DE]; Moenchsgrundstr. 19,

Published:

— with international search report

*For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.*

(54) Title: PROCESS FOR REPAIRING PUNCTURED PNEUMATIC TIRE IN TIRE-RIM ASSEMBLY AND REPAIRING SYS-
TEM

(57) Abstract: A punctured pneumatic tire in a tire-rim assembly is repaired by mounting on a vehicle the tire-rim assembly provided with an internal pressure alarm means, said tire comprising an auxiliary load-supporting structure satisfying a requirement that an deformation quantity of the tire in a radial direction thereof at a rim-assembled state under a load corresponding to 90% of a maximum load capacity at an internal tire pressure of zero is within a range of 30-60% of a section height of the tire under no load at the internal tire pressure of zero; detecting a puncture of the tire produced during the running of the tire by the internal pressure alarm means; unavoidably running the punctured tire to a relatively short-range safe place to quickly stop the vehicle; and refilling gas to a given internal pressure by a gas filling means equipped on the vehicle while occluding a punctured hole with a puncture repairing means equipped on the vehicle.



WO 2005/082646 A1